

# RM 33 ASF

## Smoke-resin remover

# PRODUCT INFORMATION

**High pressure cleaning agent for extremely intensive soilings**



### Properties:

- \* extremely powerful high pressure basic cleaning agent
- \* high cleaning activity even for low temperatures
- \* removes extreme oil/grease, tar, soot and smoke resin soilings and burned-in icings
- \* free of solvents, free of phosphates
- \* pH- value approx. 13,5 in concentrate
- \* yellowish liquid

### Fields of application:

- |                   |                    |                   |
|-------------------|--------------------|-------------------|
| * grills          | * food industry    | * bakeries        |
| * stainless steel | * canteen kitchen  | * slaughterhouses |
| * tiles           | * smoking chambers |                   |
| * ovens           | * agriculture      |                   |

### Processing:

	pre-dilution	dosing (pre-dilution)	temperature
* pre-sprayer(1)	1+9	pure	cold
* high pressure cleaning	1+3	4-8%	up to 80°C

(1) reaction time 1-5 minutes. In the food area: rinse carefully with drinking water

### Economy:

1 L RM 33 ASF is sufficient for cleaning of approx. 40 m<sup>2</sup>, presolved 1+3, dosage 4% at the high-pressure appliance, medium soiled area.

### Handling:

pre-dilution: first measure the necessary amount of water, then add RM 33 ASF under stirring and mix properly.

### Remarks:

- \* use only for materials insensitive to alkalines!
- \* do not allow to dry cleaning agent solutions on the surface.
- \* rinse machines and accessories after cleaning
- \* rinse hot water machines at minimum 2 minutes with cold water.
- \* especially in the area of sanitary and food we recommend an altering use of alkaline and acidic cleaning agents to prevent the growing of inert bacteria
- \* store frostfree

# RM 33 ASF

Smoke-resin remover

## PRODUCT INFORMATION

### Attention:

C corrosive; R35 Causes severe burns

S 1/2 Keep locked up and out of the reach of children

S 23 Do not breathe spray

S 26 In case of contact with eyes, rinse immediately with plenty of water and seek medical advice.

S36/37/39 Wear suitable protective clothing, gloves and eye/face protection.

S 45 In case of accident or if you feel unwell, seek medical advice immediately. (Show the label where possible.)

S 51 Use only in well-ventilated areas.

S 60 This material and its container must be disposed of as hazardous waste.

### Further information:

\* Material safety data sheet

### Process:

Object: e.g. smoking chambers, grill

Prespraying: apply 1+9- mixture  
reaction time 1-5 min.

Cleaning: with high-pressure, if possible hot (80°C), clear water

**Alternative:** instead of prespraying: high- pressure one step cleaning by  
1+3 pre-dilution and 8% dosage at the machine (80°C)