

# RM 57 ASF

Foam cleaner, neutral

## PRODUCT INFORMATION

**Foam cleaning agent for medium grease-, oil- and protein- containing soilings**

### Properties:

- \* removes oil, grease, protein soilings
- \* stable foam carpet
- \* good rinsing properties
- \* very gentle to materials
- \* biodegradable in accordance to OECD
- \* easily oil-,water- splitting in the oil separator (ASF)
- \* pH-value approx. 7 in concentrate
- \* clear blue liquid with characteristic odour

### Fields of application:

- \* food area
- \* butcher hall
- \* large-scale catering establishment
- \* tiles, walls
- \* water-resistant ceilings

### Processing:

	dosing	temperature
* manual	10%	cold
* high pressure	1-2%	up to 40°C
* foam nozzle	3-10%	cold
* FS 2000	10 %	cold

### Economy:

1 l RM 57 ASF is sufficient for cleaning of approx. 40 m<sup>2</sup>, dosage 1% at the high pressure appliance, medium soiled areas.

With foam generator FS 2000: 1 l is sufficient for cleaning of approx. 50 m<sup>2</sup>, dosage 10%, medium soiled areas.

### Handling:

pre-dilution: first measure the necessary amount of water, then add RM 57 ASF under stirring and mix properly.

### Remarks:

- \* rinse with drinking water in food area
- \* do not allow to dry the cleaning solution on the surface
- \* in the inside, process the product with low pressure and in well-ventilated areas
- \* store frostfree



# **RM 57 ASF**

Foam cleaner, neutral

## PRODUCT INFORMATION

### **Attention:**

- Xi Irritant; R 41 Risk of serious damage to eyes.
- S 23 Do not breathe fumes/aerosol.
- S 26 In case of contact with eyes, rinse immediately with plenty of water and seek medical advice.
- S 37/39 Wear suitable gloves and eye/face protection.
- S 51 Use only in well-ventilated areas.
- S 60 This material and its container must be disposed of as hazardous waste.

### **Certificates from neutral institutes:**

- \* DEKRA certificate of ASF efficiency

### **Further information:**

Material safety data sheet

### **System cleaning:**

#### **machine/product**

Cleaning agent-sprayer EK 1  
high pressure machine  
high pressure accessories  
foam generator FS 2000  
**RM 57 ASF Foam cleaner, neutral**

### **Process:**

- Object: e.g. large scale catering establishment, butcher halls
- \* put on steady RM 57 ASF
  - \* leave the foam up to 10 minutes, but do not allow to dry on surfaces
  - \* ringe thoroughly with high pressure