

RM 58 ASF

Foam cleaner, alkaline

PRODUCT INFORMATION

Foam cleaner agent for the cleaning of wall tiles, floor tiles and container



Properties:

- * removes oil, grease, protein soiling
- * removes food residues
- * good rinsing properties
- * enables a long time, even on vertical surfaces
- * easily biodegradable according OECD
- * easily oil-/water splitting in the oil separator (ASF)
- * pH-value approx. 13 in concentrate
- * clear yellowish liquid with characteristic odour

Fields of application:

- * food area
- * abattoir
- * container cleaning
- * large-scale catering establishment
- * tiles, walls
- * water-resistant ceilings

Processing:

	dosing	temperature
* manual	10%	cold
* high pressure cleaning	1-2%	20-60°C
* foam nozzle	4-10%	cold
* FS 2000	4-6%	cold

Economy:

1 l RM 58 ASF is sufficient for cleaning of approx. 40 m², dosage 1% at the high pressure appliance, medium soiled areas

With FS 2000, 1 l is sufficient for cleaning of approx. 75m², dosage 6%.

Handling:

pre-dilution: first measure the necessary amount of water, then add RM 58 ASF under stirring and mix properly.

Remarks:

- * rinse with drinking water in the food area.
- * do not allow to dry the cleaning agent solution on surfaces
- * when cleaning sensitive surfaces, make pretests at first
- * process the product in the inside with low pressure and good ventilation
- * store frostfree

RM 58 ASF

Foam cleaner, alkaline

PRODUCT INFORMATION

Attention:

C Corrosive; R 34 Causes burns.

S 1/2 Keep locked up and out of the reach of children

S 23 Do not breathe spray.

S 26 In case of contact with eyes, rinse immediately with plenty of water and seek medical advice.

S 28 After contact with skin, wash immediately with plenty of water.

S 36/37/39 Wear suitable protective clothing, gloves and eye/face protection.

S 45 In case of accident or if you feel unwell, seek medical advice immediately (show the label where possible)

S 51 Use only in well-ventilated areas

S 60 This material and its container must be disposed of as hazardous waste.

Further information

* Material safety data sheet

System cleaning:

machine/product:

chemical Sprayer EK 1

High pressure machine

High pressure accessories

Foam generator FS 2000

RM 58 ASF Foam cleaner, alkaline

Process:

object: e.g. large scale catering establishment, abattoir

* put on steady RM 58 ASF

* leave the foam up to 10 min., but do not allow to dry cleaning agent solution on surface

* finally rinse thoroughly with high pressure