

RM 59 ASF

Foam cleaner, acid

PRODUCT INFORMATION

Foam cleaning agent for the cleaning of wall tiles, surfaces of special steel and containers



Properties:

- * removes deposits of lime, frate, proteins, beer scale and milk scale
- * stable foam carpet
- * good rinsing properties
- * enables a long time, even on vertical surfaces
- * easily biodegradable according OECD
- * easily oil-/water splitting in the oil separator (ASF)
- * pH-value approx. 2 in concentrate
- * clear yellowish liquid with characteristic odour

Fields of application:

* abattoir * tiles, walls

* container cleaning * water-resistant ceilings

Processing:

	dosing	temperature
* manual	10%	cold
* high pressure cleaning	1-2%	20-60°C
* foam nozzle	3-10%	cold
* FS 2000	6%	cold

Economy:

1 I RM 59 ASF is sufficient for cleaning of approx. 40 m^2 , dosage 1% at the high pressure appliance, medium soiled areas.

With FS 2000, 1 I is sufficient for cleaning of approx. 75m², dosage 6%.

Handling:

pre-dilution: first measure the necessary amount of water, then add RM 59 ASF under stirring and mix properly.

Remarks:

- * rinse with drinking water in the food area.
- * do not allow to dry the cleaning agent solution on surfaces
- * when cleaning sensitive surfaces, make pretests at first
- * process the product in the inside with low pressure and good ventilation

* store frostfree

1/2 RM59/11, 06/200



RM 59 ASF

Foam cleaner, acid

PRODUCT INFORMATION

Attention:

Xi Irritant; R 36/38 Irritating to eyes and skin.

- S 23 Do not breathe spray.
- S 26 In case of contact with eyes, rinse immediately with plenty of water and seek medical advice.
- S 36/37/39 Wear suitable protective clothing, gloves and eye/face protection.
- S 51 Use only in well-ventilated areas
- S 60 This material and its container must be disposed of as hazardous waste.

Further information

* Material safety data sheet

System cleaning:

machine/product:

chemical Sprayer EK 1
High pressure machine
High pressure accessories
Foam generator FS 2000
RM 59 ASF Foam cleaner, acid

Process:

object: e.g. large scale catering establishment, abattoir

- * put on steady RM 59 ASF
- * leave the foam up to 10 min., but do not allow to dry cleaning agent solution on surface
- * finally rinse thoroughly with high pressure



Alfred Kärcher GmbH & Co. KG Alfred-Kärcher-Str. 28-40

D-71364 Winnenden Phone +49 (7195) 14-0 Fax +49 (71 95) 14 - 2212 http://www.karcher.com