

RM 750

Intensive basic cleaner

PRODUCT INFORMATION

Powerful cleaning and stripping agent for floor- and high pressure cleaning

Properties:



- * powerful floor cleaner and –stripping agent
- * strong high pressure cleaning agent
- * removes stubborn soilings, as fat, oil, soot and protein soilings
- * removes also gloss-, wax- and polymer coatings
- * free of phosphate
- * pH-value 14 in concentrate
- * clear, yellow liquid with fresh citrus odour

Fields of application:



- | | | |
|----------------|---------------------------------------|----------------|
| * industry | * factory halls | * PVC |
| * traffic area | * vehicle work shops | * stone floors |
| * agriculture | * parking houses/underground car park | |
| * food area | * super markets | |

Use and processing:

	pre-dilution	dosing (pre-dilution)	temperature
* manual	5-50%	----	up to 60°C
* floor scrubber	5-50%	----	up to 60°C
* high pressure cleaning			
heavy soiling	1+3	5%	up to 80°C
medium soiling	1+3	1%	up to 80°C

Economy:

1 l RM 750 is sufficient for the cleaning of approx. 10 m², when predilution 25%, with the floor scrubber machine.

1 l RM 750 is sufficient for the cleaning of approx. 150 m² presolved 25%, dosage 1% at the high-pressure appliance, medium soiled area.

Handling:

* measure the necessary amount of water and add RM 750 while stirring, mix properly and fill into the tank; when using large machines, make the pre-dilution separately and then put it into the tank

Remarks:

- * strong alkaline, therefore no application on alkali sensitive surfaces (like aluminium). We recommend pretests for the compatibility and resistance of materials
- * do not allow to dry cleaning agent on surfaces
- * rinse with clear water

RM 750

Intensive basic cleaner

PRODUCT INFORMATION

Attention:

C corrosive; R 34 Causes burns

S 1/2 Keep locked up and out of the reach of children

S 23 Do not breathe spray

S 26 In case of contact with eyes, rinse immediately with plenty of water and seek medical advice

S 36/37/39 Wear suitable protective clothing, gloves and eye/face protection

S 45 In case of accident or if you feel unwell, seek medical advice immediately. (Show the label where possible.)

S 51 Use only in well-ventilated areas

S 60 This material and its container must be disposed of as hazardous waste

Further information:

Material safety data sheet

Process:

* install the machine (fitting BR-/BD-accessoires) resp. HD-accessoires

* make predilution, fill into the tank

* clean the object

* clean with clear water

* apply car agents or coatings (possibly) in case of floor cleaning