

**KARCHER**

RM 751

Cement film remover

PRODUCT INFORMATION

Highly effective, acidic hardfloor cleaner

Properties:

- 
- * high acidic, powerful scrubber-basic agent
 - * solves highly effective sedimentations and scale of lime, rust, beer, milkstone and cement haze
 - * extra low foaming
 - * with corrosion protection formulation
 - * machine- (BR/BD) and manual applicable
 - * free of hydrochloric and phosphoric acid
 - * clear, reddish liquid with mild odour
 - * pH- value < 1 in concentrate

Fields of application:

- * sanitary area
- * toilettes
- * swimming pools and swimming halls
- * contract cleaners
- * outlaying floor covers
- * tiles
- * armatures

Use and processing:

	dosing	temperature
* maintenance cleaning	1-5%	cold
* basic cleaning	5-25%	cold
* removing cement haze	10-50%	cold
* removing cement haze on cast concrete stone	10-30%	cold

reaction time approx. 3-5 min.

Economy:

1 l RM 751 is sufficient for the maintenance cleaning of approx. 190 m² – when dosed 5% - medium soiled areas.

Handling:

Measure the necessary amount of water, add RM 751, mix properly and fill it into the tank; when using large machines, make the pre-dilution separately and then put it into the tank.

Remarks:

- * water the joints thoroughly with clear water
- * do not apply on marble, calciumcarbonate stone or acid sensitive surfaces
- * rinse in the food area with drinking water

**KÄRCHER**

RM 751

Cement film remover

PRODUCT INFORMATION

- * do not allow to dry cleaning agents on surfaces
- * when apply manual, wear acid resistant protective gloves
- * store frostfree

Attention:

Xi Irritant; R36/38 Irritating to eyes and skin
S 23 Do not breathe spray
S 26 In case of contact with eyes, rinse immediately with plenty of water and seek medical advice
S 36/37/39 Wear suitable protective clothing, gloves and eye/face protection
S 51 Use only in well-ventilated areas.
S 60 This material and its container must be disposed of as hazardous waste.

Further information:

Material safety data sheet

Process:

Object: e.g. new jointed tiles in e.g. toilette, swimming hall

- * water the joints thoroughly with clear water
- * apply cleaning agent solution and brush properly
- * after a reaction time of approx. 5 min., treat the surface several times with the scrubber with maximum pressure of the roller brushes
- * suck off the used dirt water
- * rinse with lots of water and brushes and suck off again.
- * after the use rinse also the machine with clear water



Alfred Kärcher GmbH & Co. KG
Alfred-Kärcher-Str. 28-40
D-71364 Winnenden
Phone +49 (7195) 14-0
Fax +49 (71 95) 14 - 2212
<http://www.karcher.com>