

RM 39 ASF

Degreaser with corrosion protection

PRODUCT INFORMATION

Cleaning – Degreasing – Corrosion protection

Properties:

- * removes oil, grease and soot soilings from metallic small and spare parts
- * temporary protection against corrosion (during interim storage)
- * gentle to materials, also for aluminium, zinc, brass
- * poor of foam
- * free of nitrite and halogenated hydrocarbons
- * pH- value approx. 10 in concentrate
- * yellowish liquid with typical odour



Fields of application:

- * car trade
- * industry
- * maintenance enterprises
- * spare-part, small part cleaning, degreasing, protection
- * degreasing of materials

Processing:

	pre-dilution	dosing (at the machine)	temperature
* high pressure cleaning	pure	2-5%	60-80°C
* part cleaning machine	pure	1-5%	40-60°C
* cleaning bath	1-5%	---	40-60°C

time of contact: 1-10 min.

Economy:

1 l is sufficient for cleaning of approx. 25 m² in case of a dosage of 1% at the high-pressure machine and of a medium degree of soiling.

Remarks:

- * the corrosion protector is water soluble. Therefore take care for quick drying after treatment and for dry storage
- * before further treatment of the surface (painting, galvanizing,...) clean carefully with hot water (high pressure)
- * orderly disposal of used leaches from the part cleaning machine.

RM 39 ASF

Degreaser with corrosion protection

PRODUCT INFORMATION

Attention:

S 23 Do not breathe spray.
S 51 Use only in well-ventilated areas

Certificates from neutral institutes:

* HWK-Düsseldorf-Certificate about absence of easily volatile halogenated hydrocarbons

Further information:

* Material safety data sheet