

# RM 55 ASF

Universal cleaner

## PRODUCT INFORMATION

**High-pressure maintenance- cleaner-concentrate for the powerful cleaning of sensitive surfaces**

### Properties:

- \* high pressure maintenance cleaning agent
- \* liquid, moderately alkaline
- \* for cleaning oil, grease and soilings of emission
- \* easily oil-/water splitting in the oil separator (ASF)
- \* very careful to surfaces
- \* applicable in all ranges of temperature
- \* good ability for dirt carrying
- \* manual applicable
- \* easily biodegradable in accordance with OECD guidelines
- \* free of phosphate
- \* pH- value approx. 10 in concentrate
- \* green liquid with fresh odour

### Fields of application:

- \* motor vehicle shops
- \* industry
- \* workshops
- \* vehicle washes
- \* motor washes
- \* cleaning of repaired parts

### Processing:

	pre-dilution	dosing (pre-dilution)	temperature
* manual	1+49	pure	cold
* pre-sprayer(1)	1+9	pure	up to 60°C
* high pressure	---	0,5-8%	up to 80°C

(1) reaction time 1-5 min. – in the food area: rinse carefully with drinking water

### Economy

1 L RM 55 ASF is sufficient for cleaning of approx. 40 m<sup>2</sup>, dosage 1% at the high-pressure appliance, medium soiled area.

### Handling:

pre-dilution: first measure the needed amount of water, then add RM 55 ASF under stirring and mix properly.

### Remarks

- \* store frost free



# RM 55 ASF

Universal cleaner

## PRODUCT INFORMATION

**Attention:**

S 2 Keep out of the reach of children

S 23 Do not breathe spray.

**Further information:**

\* Material safety data sheet

**System cleaning:**

**machine/product:**

RM-Sprayer EK1

HD-/HDS- machines

HD-/HDS- accessoires

Liquid softener RM 110 ASF

**RM 55 ASF Universal cleaner**

**Process:**

Object: e.g. Oil-/grease- soiling on a varnished sheet steel

\* 5% dosing on the machine, temperature up to 80°C

\* cleaning of the sheet steel from bottom to top in overlapped lines

\* if necessary rinse with clear water