

RM 754

Stripping agent, Lino

PRODUCT INFORMATION

mild and effective stripping agent - preferable processing with floor scrubbers -

Properties:

- * careful and mild cleaning agent for removing coatings
- * usable for manual cleaning
- * removes shiny, wax and polymer coatings
- * free of solvents
- * pH-value approx. 10 in concentrate
- * clear, green liquid

Fields of application:

- * offices
- * shopping centres
- * stores
- * linoleum
- * all water-resistant hard surfaces

Processing:

- | | dosing | temperature |
|-------------------------------|---------------|--------------------|
| * maintenance cleaning | 1 - 3 % | up to 60°C |
| * basic cleaning ¹ | 20-50 % | up to 60°C |
- ¹ reaction time approx. 10 – 15 minutes

neutralize with clear water after the basic cleaning.

Economy:

for the application with floor- scrubber machines at a dilution of 25%, 1 l RM 754 is sufficient for the basic cleaning of approx. 10 m².

Handling:

at first put water into the tank and then add cleaning agent and mix it; when using large machines, make the predilution separately and then put into the tank.

Remarks:

- * medium alkaline, carry out preliminary tests before cleaning very sensitive surfaces
- * no application on wood or unsealed parquet
- * store frostfree



RM 754

Stripping agent, Lino

PRODUCT INFORMATION

Attention:

- Xi Irritant; R 36 Irritating to eyes
- S 2 Keep out of the reach of children
- S 23 Do not breathe fumes/aerosol.
- S 24 Avoid contact with skin
- S 26 In case of contact with eyes, rinse immediately with plenty of water and seek medical advice.
- S 51 Use only in well-ventilated areas
- S 60 This material and its container must be disposed of as hazardous waste.

Further information:

- * Material safety data sheet

Cleaning with system:

machine/product

BR-/BD-scrubber

BR-/BD-accessoires

basic cleaning:

basic cleaning/delayering

RM 752

basic floor cleaner

RM 69 ASF ES

maintenance cleaning:

wipe care

RM 745

basic cleaner/stripping agent Lino

RM 754

Process:

object: e.g. PVC floor

- * remove rough dirt by sweeping
- * install the machine (fitting BR-/BD-accessoires)
- * make predilution (25%), fill into the tank
- * clean the object
- * neutralize with clear water