

Product Information

RM 781

Special Coating

Sturdy coating with silky lustre for hard surfaces.
Slide-restraining certificate according to DIN V 18032-2: 2001- 04



Features:

- * high-quality coating containing waxes
- * silky lustre
- * strainable
- * slide-restraining
- * able to polish
- * pH 7,0, concentrate
- * white solution; characteristic odour

Application Range:

- * Office
- * Shopping mall
- * Sports hall
- * Kindergarden
- * Multipurpose hall
- * Linoleum
- * PVC
- * School

Advice for the application:

	Dosage
* RM 781	pur

Fertility:

1 litre RM 781 is enough for 8 m²

Advice:

- * do not apply to wood or unsealed parquet
- * do not apply to "fine stone ware"
- * frost-protected store
- * for the maintenance cleaning please take our product RM 780 Wipe Care

Attention:

S 51 Do not breathe fumes/aerosol

Further information:

- Material safety data sheet
- Certificate

Processing:

Object: e.G. PVC- floor

- remove stones with a broom
- basic cleaning resp. stripping with RM 752 or RM 754 (linoleum); dosage: 10-50%
- apply manual a thin layer RM 781 pure and equal with a moist Mopp on the based cleaned, neutralized and dry floor
- let dry approx. 1 h in well ventilated room
- if required 3 layer application pure, manual
- careful passable after 30 min. drying time
- completely hardened and passable after 24 h