

# RM 803 ASF

Prewash

# PRODUCT INFORMATION



RM 803 ASF is an alkaline concentrated **detergent for high pressure and prespraying application of cars and commercial vehicles** and for dissolving stubborn contaminations.

This alkaline detergent enhances presoaking and removal of many kinds of stubborn dirt like oil, grease and insect residues. RM 803 ASF is specially designed for high pressure cleaning/ prewash in brush wash plants, hp gantry plants, high pressure wash in coin-op plants and prespraying devices.

Some further advantages: RM 803 ASF is easily biodegradable in accordance with EEC 648/2004 guidelines. Additionally RM 803 ASF shows the easy to separate properties and does not affect the efficiency of oil separators.



## Instructions for application:

Type of plant	Predilution (RM + water)	Application strength based on original concentrate
brush wash plant	undiluted	0,5 to 2 %
coin-op plant	1 + 2	0,5 to 2 %
hp device	1 + 2	0,5 to 2 %
prespraying device	1 + 49	2 %

*Time to effect:* max. 1-5 minutes

*Temperature:* max. 140 °C

**Do not allow to dry on!**

**Perform tests on alkali sensitive surfaces in advance!**

**Store in a frost-proof place!**

pH-value concentrate: approx. 13

## Further information:

Material Safety Data Sheet

### Attention:

C- Corrosive; R 34 Causes burns.

S 23 Do not breathe spray.

S 26 In case of contact with eyes, rinse immediately with plenty of water and seek medical advice.

S 28 After contact with skin, wash immediately with plenty of water.

S 36/37/39 Wear suitable protective clothing, gloves and eye/face protection.

S 45 In case of accident or if you feel unwell, seek medical advice immediately. (Show the label where possible).

S 51 Use only in well-ventilated areas.

S 60 This material and its container must be disposed of as hazardous waste.