

RM 821 ASF

Spray Wax

PRODUCT INFORMATION



RM 821 ASF is a liquid **spray wax with preservative and polishing properties** for the application in vehicle washing plants, coin-op plants and high pressure devices.

A spot-free drying without blower is obtained with the combination osmotic water and RM 821 ASF.

The coating has long-time preservative and water repellent properties.

RM 821 ASF is free from mineral oils and hydro carbons.

RM 821 ASF is easily biodegradable in accordance with EEC 648/2004. RM 821 ASF does not affect the efficiency of oil separators.



Instructions for application:

Type of plant	Predilution (RM +demineralized water)	Application strength based on original concentrate
brush wash plant	undiluted	0,1 to 0,2 %
coin-op plant	depends on typ of plant	0,1 to 0,2 %
hp device	1 + 9	0,1 to 0,2 %

Temperature: max. 80 °C

Store in a frost-proof place!

Avoid overdosing!

Do only apply on clean and rinsed off surfaces!

Use only with demineralized water for predilution!

pH-value concentrate: approx. 4

Further information:

Material Safety Data Sheet

Attention:

R 52/53 Harmful to aquatic organism, may cause long-term adverse effects in the aquatic environment

S 23 Do not breathe spray

S 24 Avoid contact with skin

S 51 Use only in well- ventilated areas

S 60 This material and its container must be disposed of as hazardous waste.

Contains (R)-p-mentha-1,8-diene. May produce an allergic reaction.