

# RM 828 ASF

## Active drying agent

# PRODUCT INFORMATION



RM 828 ASF is a concentrated **Active Dryer with thermowax properties** for the application in vehicle washing plants with blower as chemical drying aid.

RM 828 ASF shows a quick break-down of the water film and a gentle long-time preservation with water-repellant and polishing effect.

RM 828 ASF is free from mineral oils and hydro carbons.

Some further advantages: RM 828 ASF is easily biodegradable in accordance with EEC 648/2004. Additionally RM 828 ASF does not affect the efficiency of oil separators.

### Instructions for application:

Type of plant	Predilution (RM + demin. water)	Application strength based on original concentrate
brush wash plant	undiluted	0,1 to 0,2 %
HP-gantry wash plant	undiluted	0,1 to 0,2 %

Temperature: max. 80 °C

**Store in a frost-proof place!**

**Avoid overdosing!**

**Do only apply on clean and rinsed off surfaces!**

**Without blower a subsequent rinsing step with osmotic water is recommended!**

pH-value concentrate: approx. 6

### Further information:

Material Safety Data Sheet

### Attention:

Xi Irritant; R 38/38 Irritating to skin and eyes;

N Dangerous for the environment; R 51/53 Toxic to aquatic organisms, may cause long-term adverse effects in the aquatic environment

S 23 Do not breathe aerosol

S 26 In case of contact with eyes, rinse immediately with plenty of water and seek medical advice

S 37/39 Wear suitable gloves and eye/face protection

S 51 Use only in well-ventilated areas

S 60 This material and its container must be disposed of as hazardous waste

S 61 Avoid release to the environment. Refer to special instructions /safety data sheets.